

MIX-N-FIX XL

MIX-N-FIX XL is a waterproof, thick/thin bed material made from cement, the finest aggregates and the best quality additives. It is specifically formulated to bond a variety of tiles onto rigid substrates. The use of Mix-n-Fix XL would ensure an excellent bonding for your tiling or cladding jobs.

TYPICAL PROPERTIES

- Appearance : Powder
- Colour : Grey

ADVANTAGES



Soaking of tiles in water is not essentially needed.



Tiles direct from the box, can be fixed on the desired surface, minimising possible breakage & labour cost on soaking.



Wetting of the surface to be tiled is not necessary as Mix-n-Fix XL works perfectly on clean & dry surfaces. However, washing a surface to clean & remove loose particles, etc is recommended ½ hour prior to the fixing. Curing is not required as Mix-n-Fix XL is self-curing. Hacking or roughening of the surface to be tiled is not necessary.



Mix-n-Fix XL waterproofs the entire surface it is applied upon.

METHOD OF USE

Mix-n-Fix XL can be used on both walls and floors, in interior and exterior applications. Mix-n-Fix XL is highly recommended for the thick/thin bed-fixing of a variety of tiles. Mix-n-Fix XL can be used to fix tiles on to concrete, cement renders/screeds and rendered brickwork. Mix-n-Fix XL can also be used to fix dense, vitreous ceramic tiles, marbles, granites, etc. by adding ZORISCOTT* in the mixing water. 1 part ZORISCOTT & 4 parts clean water should be mixed, and this mixed solution should be used with Mix-n-Fix XL for fixing dense tiles.

APPLICATION INSTRUCTIONS

Spread the creamy mortar onto the surface using a notched trowel to a thickness of 2-3 mm. Tiles must be coated with the creamy mortar (like coating butter on bread) and fixed on the mortar-applied surface. The final bed thickness for wall tiles is minimum 2 mm whilst for floor-tiling, a minimum bed thickness of 3 mm is recommended. At any one time, do not spread more than one sq. metre of mortar on the surface. Tiles must be pressed firmly into position before the mortar skins. Make sure that all the tiles are well-bedded and there are no voids under the tiles. Once the tiles have been fixed, they must not be disturbed for 24 hours.

SURFACE PREPARATION

All surfaces should be structurally sound, clean, dry and free from oil, grease or any other loose materials. Newly rendered/screeded surfaces should be allowed to cure for at least 10-15 days. New concrete must be cured for 4 weeks. Steel trowel well finished concrete must be mechanically abraded prior to tiling. Porous surfaces should be primed/sealed using a cement fortifier (ZORISCOTT)*.

MIXING

Add Mix-n-Fix XL to a bucket containing clean water, mixing uniformly/constantly to achieve the required thick, creamy consistency. The mixing ratio is 25 kg of Mix-n-Fix XL approximately to 5.5-6.5 litres of water. Allow the mixed creamy paste to stand for 5-10 minutes, remix and it is ready for use.

GROUTING

Grout joints of 1-5 mm width can be grouted with COLOR TILEWALLA. For larger grouts that are 5-12 mm wide, use a special bonding agent ZORISCOTT* for increased water resistance & flexibility.

CLEAN-UP

Remove any excess mortar from the face of the tile using a damp cloth, while the mortar is still in the wet condition. Tools & equipment should be cleaned with water before the mortar dries.

PRECAUTIONS

Do not allow the applied material to skin prior to tiling. In case of skin formation, remove the same and dispose, then re-apply a fresh material. ZORISCOTT should be used with Mix-n-Fix XL when tiling areas where ponded water and continual immersion occurs i.e. swimming pools, spas, etc.

PACKAGING

5kg, 20kg & 30 kg bag.

SHELF LIFE

Upto 12 months in unopened bags, when stored in cool, dry conditions.

SERVICES

For further information on this product and its application, please contact the Technical Services Department of Nerofix Pvt. Ltd.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

NEROFIX PRIVATE LIMITED

REGD. OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI - 400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR
CONTACT THE MANAGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com