

TURBOFIX SPFM-M

TURBOFIX SPFM-M is a high quality, high solids, sprayable contact adhesive, featuring very high green strength coupled with an excellent working tack life. TURBOFIX SPFM-M is suitable for bonding foam to decorative laminates, most woods, MDF and particle boards as well as steel, aluminum, plasterboards, high density foams, rexine, plywood, etc. It is primarily used in the furniture manufacturing industry.

RECOMMENDED USAGE

Specially designed for easy spraying without cobwebbing, TURBOFIX SPFM-M is suitable for use with all the current post-forming equipment.

FEATURES & BENEFITS



Fast-drying



Very high green strength



High solids

TYPICAL PHYSICAL PROPERTIES

- Type : Contact type sprayable adhesive
- Colour : Light yellow (L 2.0 ASTM)

PACKAGING

Available in 1, 5, 30 and 200 Litre containers.

PREPARATION

TURBOFIX SPFM-M is applied with suction feed or pressure pot equipment. Prior to application, ensure all surfaces are clean, dry and free of oil and grease.

APPLICATION

Apply an even film of adhesive to both surfaces. Allow them to dry for approx. 0.5 to 3 minutes (depending on weather conditions) or until they can be touched with the knuckles without any adhesive being transferred. Align the surfaces accurately, and then join them (take care not to entrap air) with as much pressure as possible.

In some cases, highly porous substrates may require 2 coats. Bonding of materials should occur within 60 minutes; if left longer, a light spray coat should be reapplied to reactivate the surfaces.

SAFETY PRECAUTIONS



Store away from heat sources and naked flames; keep under cover and well-ventilated. The solvents are highly flammable. Keep the container lid tightly closed when not in use.

STORAGE AND SHELF LIFE

It should be stored in well-sealed containers, under dry conditions below 30°C. TURBOFIX SPFM-M will keep satisfactorily for 12 months from the date of manufacture. Low or high temperature storage should be avoided.

SERVICES

For further information on this product and application please contact Technical Services Department of Nerofix Pvt. Ltd.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any

NEROFIX PRIVATE LIMITED

REGD OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI-400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR
CONTACT THE MANGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com