

KRACKSEAL-XL

KRACKSEAL-XL is a unique, elastomeric & immensely useful product. **KRACKSEAL-XL** is an acrylic-based component and a sealing compound of white colour. The product is a remarkably cohesive, creamy paste of high plasticity for easy application, deeper penetration, excellent bonding and fully water resistant.

TYPICAL PROPERTIES

- Appearance : Viscous liquid
- Colour : White

ADVANTAGES



Single component acrylic based, white putty.



Very low shrinkage, non-staining.



Can be used/applied on damp surfaces, structures in damp conditions



No cracking or crumbling.



Extremely useful for sealing of cracks, holes, gaps, joints in ceramic, wood, glass, metal, aluminium windows, cement/concrete and CI/cement pipes.



All conventional paints can be applied over, after being fully cured.



Highly elastic, gives a durable performance in wide temperature variations.



Long lasting, water resistant and durable.



Useful in minor expansion & contraction joints.



Excellent adhesion & bonding capacity with cement/concrete, wood and metal.

APPLICATION INSTRUCTIONS

- Remove dirt, dust, loose particles, oil & grease from the joints & cracks using a wire brush, with plenty of water to wash down the said particles etc., and to moisten the surface as well.
- Widen small narrow cracks & joints and make them U shaped with the increased depth to ensure deeper penetration, proper filling and bonding of **KRACKSEAL-XL**

AREA OF USAGE

- Filling and sealing of cracks and holes in roofs, terraces, water tanks etc. for stopping leakage & seepage completely.
- Gaps between masonry/concrete structures and aluminium windows, doors, wooden door frames and windows.
- Joints in cast iron, cement pipes.
- Filling the gaps/holes in AC sheets for 'J' bolt.
- Permanent & firm filling of the cavities behind wash basins, sinks, bath tubs.
- Sealing and plugging of structural joints.
- Repairing damaged and decaying structures.
- Plugging the gaps and cavities in between precast structures.
- Leak-proof filling of precast pipe joints.

DIRECTIONS FOR USE

Use wet spatula, putty knife to fill the gap, joints & cracks. Care should be taken to ensure that no voids, cavities or air bubbles are formed while applying/filling. Level the surface with a wet spatula/putty knife and allow drying/curing for a period of 24-72 hours. In case treated cracks/joints/gaps show any shrinkage after the drying, the same should be topped up to the desired level and allowed it to dry.

PRECAUTION

Application not recommended while raining or when rain is forecasted. Do not use below waterline application. Store away from extreme heat or cold

CLEANING OF TOOLS & HANDS

Hands & tools can be cleaned conveniently with the help of soap & water.

PACKAGING

KRACKSEAL-XL is available in 500 grams, 1 kg & 5 kg packs.

SHELF LIFE

At least 12 months from the date of manufacture in the original sealed condition.

STORAGE

Low or high temperature storage should be avoided and the adhesives should preferably be stored within the temperature range of +5°C up to +35°C.

SERVICES

For further information on this product and its application, please contact the Technical Services Department of Nerofix Pvt. Ltd.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results. The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

NEROFIX PRIVATE LIMITED

REGD. OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI -400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR CONTACT THE MANAGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com