

SCOTTPROOF WALLCOAT

SCOTTPROOF WALLCOAT is an acrylic, elastomeric waterproof coating, cold applied & self-curing for effective water control, and moisture & water penetration for vertical surfaces.

Improved elongation properties of the cured membrane covers/bridges the minute cracks, performs well over a wide temperature range and stays unaffected in marine conditions.

TYPICAL PROPERTIES

- Appearance : Viscous liquid
- Colour : As per requirement

ADVANTAGES



Single component, ready -to-use, white colour. Self curing.



Resistance to UV light



High resistance to fungus



Scottproof wall coat can be mixed with universal strainers for desired colour shades. It can be applied by brush.

AREA OF USAGE

Designed for all structural concrete in contact with water such as:

- Waterproofing of vertical walls, etc.
- Waterproofing of external vertical walls and chajjas basements of buildings.
- Waterproofing of stone walls/bricks/wood etc.
- Waterproofing of corrugated AC sheets, roofing/metal sheets, etc.
- Joint-less and seamless membrane waterproofing with moderate heat insulation.

PACKAGING

Available in 2, 5, 20, 30kg containers

SAFETY PRECAUTIONS

In case it comes in contact with eyes, wash the eyes with plenty of water. If irritation persists, consult a medical practitioner.

SHELF LIFE

At least 12 months from the date of manufacture in the original sealed condition.

STORAGE

Low or high temperature storage should be avoided and the adhesives should preferably be stored within the temperature range of +5°C up to +35°C.

SERVICES

For further information on this product and its application, please contact the Technical Services Department of Nerofix Pvt. Ltd.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

NEROFIX PRIVATE LIMITED

REGD. OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI -400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR CONTACT
THE MANAGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com