

TURBOFIX PVC GRIP

TURBOFIX PVC GRIP is a synthetic resin-based adhesive compounded by proprietary additives. It has a unique formulation that maintains a strong bond. It is specially designed for bonding PVC to wood, MDF, plywood, etc.

TYPICAL PROPERTIES

- Appearance : Viscous liquid
- Colour : Milky white

ADVANTAGES



Excellent bonding for wood to PVC & wood to Acrylic



Higher coverage & easy spreadability



High strength with long & durable bonding



Excellent heat resistance



Phthalate-free product



Low VOC content

AREA OF USAGE

Furniture Industries

- Ply to PVC laminates
- Ply to acrylic
- PVC laminates to MDF/particle boards and other cellulosic material

APPLICATION INSTRUCTIONS

- Ensure that the surface is free from oil, dust and any other contaminants.
- Ensure that the surface is properly leveled. Rough the surface by sand paper and clean it.
- Stir the glue for a homogeneous mixture. Apply the uniform coat of glue on laminates and then plywood.
- Bring both the surfaces in contact and make proper alignments. Start pressing from one side by using wet clothes to avoid any air bubbles.
- Pressure can be given by a nail, clamp, weight, press machine or a masking tape.
- Remove and clean the excess material that oozes out from the surface's side.
- Keep the bonded surface under pressure for 24 hours.

PRECAUTIONS



1. Ensure that the moisture content in the substrate is below 12%.
2. The application temperature should be above +5°C.
3. Close the container after use to prevent skin formation.

SHELF LIFE

Best before one year from the date of manufacturing if stored under cool and dry conditions in a sealed container.

STORAGE

Low or high temperature storage should be avoided and the adhesives should preferably be stored within the temperature range of +5°C to +35°C.

SERVICES

For further information on this product and its application, please contact the Technical Services Department of Nerofix Pvt. Ltd.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

NEROFIX PRIVATE LIMITED

REGD. OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI - 400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR
CONTACT THE MANAGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com