

TURBOFIX-SPAS (P)

TURBOFIX-SPAS (P) is a high quality, high solids, sprayable synthetic rubber contact adhesive, featuring very high early green strength coupled with an excellent working tack life. Turbifix SPAS(P) is suitable for bonding decorative laminates, most woods, MDF and particle boards as well as steel, aluminium, plasterboards, high density foams, rexene, plywood, etc. It is primarily used in the furniture manufacturing industry, where extra heat resistance, uninterrupted spraying and the ability to be used at temperatures from 15-30°C is required. Turbifix SPAS(P) also gives excellent adhesion to a wide range of materials including many natural and synthetic rubbers, rigid and flexible polyurethane foams and other similar materials.

TYPICAL PROPERTIES

- Appearance : Viscous liquid
- Colour : Yellow

ADVANTAGES



Fast-drying



Very high green (initial) strength



High solids

PREPARATION

Turbifix SPAS(P) is applied with a suction feed or a pressure pot equipment. Prior to its application, ensure that all the surfaces are clean, dry and free of oil and grease.

RECOMMENDED USES

Specially designed for easy spraying without cobwebbing, Turbifix SPAS (P) is suitable for use with all the current post-forming equipment.

COVERAGE

Approximately 8-10 m² per litre on one surface.

APPLICATION INSTRUCTIONS

Apply an even film of adhesive to both surfaces. Allow them to dry for approximately 2 - 20 minutes (depending on weather conditions) or until they can be touched with the knuckles without any adhesive being transferred. Align the surfaces accurately, and then join them (take care not to entrap air) with as much pressure as possible.

In some cases, very porous substrates may require 2 coats. Bonding of materials should occur within 45 minutes – if left longer, a light spray coat should be reapplied to reactivate the surfaces.

SAFETY PRECAUTIONS

Store away from heat sources and naked flames, under cover and well-ventilated. The solvents are highly flammable.

PACKAGING

Available in 30 L and 200 L drums.

SHELF LIFE

When stored in well-sealed containers, Turbifix SPAS (P) will keep satisfactorily for 12 months from the date of manufacturing.

STORAGE

Low or high temperature storage should be avoided and the adhesives should preferably be stored within the temperature range +5°C upto +35°C.

SERVICES

For further information on this product and its application, please contact NEROFIX PVT.LTD. – Technical Services Department.

IMPORTANT NOTICE

Whilst all reasonable care is taken in the compilation of this data sheet, it is the customer's responsibility to determine the suitability of the product for the desired application.

DISCLAIMER

KANSAI NEROLAC PAINTS LTD. (KNPL) warrants that all products are free from any defects of manufacturing and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of NEROLAC. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full-scale usage of KNPL products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the product or refund of the purchase price paid, if any product is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

NEROFIX PRIVATE LIMITED

REGD. OFFICE: 111, THE GREAT EASTERN GALLERIA, PLOT NO. 20, SECTOR -4 NERUL (WEST),
NAVI MUMBAI - 400706, MAHARASHTRA, INDIA

FOR CONSUMER COMPLAINTS AND FEEDBACK, REFER TO THE REGD. OFFICE OF NEROFIX PRIVATE LIMITED OR
CONTACT THE MANAGER, CONSUMER CARE CELL AT: 8291715780 OR EMAIL TO: customercare@nerofixindia.com